

DECLARATION OF PERFORMANCE (DoP: HED-001)**Construction Products Regulation (EU) No 305/2011**

Product type: HERTALED, HERTALED FA

Type, batch or serial number: See product or packaging

Intended Use: Damp proof course, EN 14909

Contact data producer: Carlisle Construction Materials BV
Industrieweg 16
NL-8263 AD KAMPEN

AVCP: 3

Notified body (hEN): KIWA n.v., Sir W. Churchillaan 273, NL-2288 EA Rijswijk
Notified body no.: 0620
FPC: 0620-CPR-44520

Declared performance:

Essential characteristics	Performance	Test standard	Harmonised technical standard
Reaction to fire	Class E	EN 13501-1	EN 14909: 2012
Watertightness	Pass	EN 1928	
Resistance to impact (mm)	npd	EN 12691	
Low temperature flexibility (°C)	npd	EN 495-5	
Durability (artificial ageing)	Pass	EN 1928 / EN 1296	
Durability (alkali)	Pass	Annex C	
Dangerous substances	Meets requirements		

Declaration

The performance of the product is in conformity with the declared performance. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Bart Smit, R&D manager

Kampen, January 2017

